



BULB, SPOT AND PAR LAMPS SERIES



BJM-CA-HP-3W-TT
BJM-CA-HP-3W-PT



BBT-BL-DLS5W



BBT-BL-DLS7W
BBT-BL-DLS9W



BBT-BL-DLS12W



BBT-BL-DLS15W



BBT-BL-DLS18W

Model	LED Power	Input Voltage	LED Chip Type / Brand	CRI (Ra)	Color Temperature	Lumen	Beam Angle	Dimension	Base Type	SRP as of JUNE 2017
BJM-CA-HP-3W-PT	3W	AC85-265V	HPLED BRIDGELUX	WW>80 PW>70	2400K~6500K	240-270Lm	120°	H-125mm D-40mm	E14 E27	375.00
BJM-CA-HP-3W-TT										375.00
BBT-BL-DLS5W	5W	AC85-265V	SMD5730 EPISTAR	WW>80 PW>75	2700K-6000K	540-600Lm	190°	H-110mm D-58mm	E27	750.00
BBT-BL-DLS7W	7W	AC85-265V	SMD5730 EPISTAR	WW>80 PW>75	2700K-6000K	630-700Lm	150°	H-117mm D-63mm	E27	850.00
BBT-BL-DLS9W	9W	AC85-265V	SMD5730 EPISTAR	WW>80 PW>75	2700K-6000K	810-900Lm	150°	H-117mm D-63mm	E27	980.00
BBT-BL-DLS12W	12W	AC85-265V	SMD5730 EPISTAR	WW>80 PW>75	2700K-6000K	1080-1200Lm	150°	H-125mm D-63mm	E27	1000.00
BBT-BL-DLS15W	15W	AC85-265V	SMD5730 EPISTAR	WW>80 PW>75	2700K-6000K	1350-1500Lm	190°	H-150mm D-80mm	E27	1450.00
BBT-BL-DLS18W	18W	AC85-265V	SMD5730 EPISTAR	WW>80 PW>75	2700K-6000K	1620-1800Lm	150°	H-150mm D-80mm	E27	1950.00



1W & 3W MR11



BBL-SP-3W-DC
BBL-SP-3W-AC



BBL-SP-6W-DC
BBL-SP-6W-AC



BLD-PAR30A-12W



BLD-PAR30A-15W



BLD-PAR30A-18W
BLD-PAR30A-21W

Model	LED Power	Input Voltage	LED Qty.	LED Chip Type / Brand	CRI (Ra>)	Color Temperature	Lumen	Size	Beam Angle	Base Type	SRP as of JUNE 2017
BJM-MR11-1WDC12	1W	DC12V	1pc	HPLED BRIDGELUX	WW>80 PW>70	2400K~6500K	80-90Lm	H-37mm D-35mm	15°, 30° 45°	MR11	350.00
BJM-MR11-3WDC12	3W	DC12V	1pc	HPLED BRIDGELUX	WW>80 PW>70	2400K~6500K	240-270Lm	H-37mm D-35mm	15°, 30° 45°	MR11	375.00
BBL-SP-3W-DC BBL-SP-3W-AC	3W	DC12V AC85-265V	3pcs	HPLED BRIDGELUX	WW>80 PW>70	2400K~6500K	240-270Lm	H-65mm D-50mm	15°, 30° 45°	MR16 E27 GU10	375.00
BBL-SP-6W-DC BBL-SP-6W-AC	6W	DC12V AC85-265V	3 X 2W	HPLED BRIDGELUX	WW>80 PW>70	2400K~6500K	480-540Lm	H-76mm D-50mm	15°, 30° 45°	MR16 E27 GU10	600.00
BLD-PAR30A-12W	12W	AC85-240V	1pc	COB EPISTAR	WW>80 PW>70	2700K~6500K	1080-1200Lm	D=92mm H=103mm	15°/24° 60°	E27	1,650.00
BLD-PAR38A-15W	15W	AC85-240V	1pc	COB EPISTAR	WW>80 PW>70	2700K~6500K	1350-1500Lm	D=122mm H=130mm	15°/24° 60°	E27	2,250.00
BLD-PAR38A-18W	18W	AC85-240V	1pc	COB EPISTAR	WW>80 PW>70	2700K~6500K	1620-1800Lm	D=122mm H=130mm	15°/24° 60°	E27	2,550.00
BLD-PAR38A-21W	21W	AC85-240V	1pc	COB EPISTAR	WW>80 PW>70	2700K~6500K	1890-2100Lm	D=122mm H=130mm	15°/24° 60°	E27	2,950.00



HPLED AND COB DIRECTIONAL CEILING DOWN LIGHT SERIES



BBL-CL-HP-3W



BBL-CL-HP-5W



BBL-CL-HP-7W



BBL-CL-HP-9W



BBL-CL-HP-12W



BBL-CL-HP-15W



BPS-CL-5W-C2



BPS-CL-7W-C2



BPS-CL-9W-C2



BPS-CL-12W-C2



BPS-CL-15W-C2



BPS-CL-20W-C2



BPS-CL-5W-SC2



BPS-CL-7W-SC2




BPS-CL-9W-SC2



BPS-CL-12W-SC2



BPS-CL-15W-SC2



BPS-CL-20W-SC2

Model	LED Power	Input Voltage	LED Qty.	LED Chip / Driver	CRI (Ra>)	Color Temperature	Lumen	Beam Angle	Dimension	SRP as of JUNE 2017
BBL-CL-HP-3W	3W	AC85-265V	3pcs	HPLED BRIDGELUX CE APPROVED DRIVER	WW>80 PW>70	2400K-6500K	240-270Lm	15°, 30° 45°, 60°	D-85mm - H-40mm Cut-Out - 70mm	650.00
BBL-CL-HP-5W	5W	AC85-265V	5pcs		WW>80 PW>70	2400K-6500K	400-450Lm	15°, 30° 45°, 60°	D-110mm - H-45mm Cut-Out - 92mm	1,150.00
BBL-CL-HP-7W	7W	AC85-265V	7pcs		WW>80 PW>70	2400K-6500K	560-630Lm	15°, 30° 45°, 60°	D-110mm - H-45mm Cut-Out - 92mm	1,300.00
BBL-CL-HP-9W	9W	AC85-265V	9pcs		WW>80 PW>70	2400K-6500K	720-810Lm	15°, 30° 45°, 60°	D-137mm - H-43mm Cut-Out - 118mm	1,650.00
BBL-CL-HP-12W	12W	AC85-265V	12pcs		WW>80 PW>70	2400K-6500K	960-1080Lm	15°, 30° 45°, 60°	D-137mm - H-43mm Cut-Out - 118mm	1,900.00
BBL-CL-HP-15W	15W	AC85-265V	15pcs		WW>80 PW>70	2400K-6500K	1200-1350Lm	15°, 30° 45°, 60°	D-138mm - H-72mm Cut-Out - 118mm	3,700.00
BPS-CL-5W-C2 BPS-CL-5W-SC2	5W	AC85-265V	1pc	CREE Chip LIFUD Driver	WW>80 PW>70	3000K-6000K	450-500Lm	30°, 40° 60°, 90°	92mm - 92mm Cut-Out - 75mm	1,750.00
BPS-CL-7W-C2 BPS-CL-7W-SC2	7W	AC85-265V	1pc		WW>80 PW>70	3000K-6000K	630-700Lm	30°, 40° 60°, 90°	92mm - 92mm Cut-Out - 75mm	1,800.00
BPS-CL-9W-C2 BPS-CL-9W-SC2	9W	AC85-265V	1pc		WW>80 PW>70	3000K-6000K	810-900Lm	30°, 40° 60°, 90°	92mm - 92mm Cut-Out - 75mm	1,900.00
BPS-CL-12W-C2 BPS-CL-12W-SC2	12W	AC85-265V	1pc		WW>80 PW>70	3000K-6000K	1080-1200Lm	30°, 40° 60°, 90°	92mm - 92mm Cut-Out - 75mm	2,050.00
BPS-CL-15W-C2 BPS-CL-15W-SC2	15W	AC85-265V	1pc		WW>80 PW>70	3000K-6000K	1350-1500Lm	30°, 40° 60°, 90°	92mm - 92mm Cut-Out - 75mm	2,430.00
BPS-CL-20W-C2 BPS-CL-20W-SC2	20W	AC85-265V	1pc		WW>80 PW>70	3000K-6000K	1800-2000Lm	30°, 40° 60°, 90°	92mm - 92mm Cut-Out - 75mm	2,800.00

Prices are subject to change without prior notice.



COB DIRECTIONAL GRILLE/GIMBAL DOWNLIGHT OPEN TYPE



BPS-GL-1X12W-GC
BPS-GL-1X15W-GC



BPS-GL-1X20W-GC
BPS-GL-1X30W-GC



BPS-GL-2X12W-GC
BPS-GL-2X15W-GC



BPS-GL-2X20W-GC
BPS-GL-2X30W-GC



BPS-GL-3X12W-GC
BPS-GL-3X15W-GC



BPS-GL-3X20W-GC
BPS-GL-3X30W-GC

Model	LED Power	Input Voltage	LED Qty.	LED Chip / Driver	CRI (Ra>)	Color Temperature	Lumen	Beam Angle	Dimension	SRP as of JUNE 2017
BPS-GL-1X12W-GC	12W	AC100-240V	1pc	CITIZEN COB LIFUD DRIVER	WW>80 PW>72	3000K-5000K	1140-1260Lm	13° 23° 38°	L=190mm W=190mm H=80mm Cut-out=160mm * 160mm	2,700.00
BPS-GL-1X15W-GC	15W	AC100-240V	1pc		WW>80 PW>72	3000K-5000K	1425-1575Lm			2,800.00
BPS-GL-1X20W-GC	20W	AC100-240V	1pc		WW>80 PW>72	3000K-5000K	1900-2100Lm			3,900.00
BPS-GL-1X30W-GC	30W	AC100-240V	1pc		WW>80 PW>72	3000K-5000K	2850-3150Lm			4,250.00
BPS-GL-2X12W-GC	24W	AC100-240V	2pcs	CITIZEN COB LIFUD DRIVER	WW>80 PW>72	3000K-5000K	2280-2520Lm	13° 23° 38°	L=345mm W=190mm H=80mm Cut-out=320mm * 160mm	4,950.00
BPS-GL-2X15W-GC	30W	AC100-240V	2pcs		WW>80 PW>72	3000K-5000K	2850-3150Lm			5,100.00
BPS-GL-2X20W-GC	40W	AC100-240V	2pcs		WW>80 PW>72	3000K-5000K	3800-4200Lm			7,000.00
BPS-GL-2X30W-GC	60W	AC100-240V	2pcs		WW>80 PW>72	3000K-5000K	5700-6300Lm			7,900.00
BPS-GL-3X12W-GC	36W	AC100-240V	3pcs	CITIZEN COB LIFUD DRIVER	WW>80 PW>72	3000K-5000K	3420-3780Lm	13° 23° 38°	L=495mm W=190mm H=80mm Cut-out=480mm * 160mm	7,100.00
BPS-GL-3X15W-GC	45W	AC100-240V	3pcs		WW>80 PW>72	3000K-5000K	4275-4725Lm			7,350.00
BPS-GL-3X20W-GC	60W	AC100-240V	3pcs		WW>80 PW>72	3000K-5000K	5700-6300Lm			9,650.00
BPS-GL-3X30W-GC	90W	AC100-240V	3pcs		WW>80 PW>72	3000K-5000K	8550-9450Lm			11,700.00

Prices are subject to change without prior notice.



BPS-GL-1X12W-B
BPS-GL-1X20W-B



BPS-GL-1X30W-B
BPS-GL-1X40W-B



BPS-GL-2X12W-B
BPS-GL-2X20W-B



BPS-GL-2X30W-B
BPS-GL-2X40W-B



BPS-GL-3X12W-B
BPS-GL-3X20W-B



BPS-GL-3X30W-B
BPS-GL-3X40W-B

Model	LED Power	Input Voltage	LED Qty.	LED Chip / Driver	CRI (Ra>)	Color Temperature	Lumen	Beam Angle	Dimension	SRP as of JUNE 2017
BPS-GL-1X12W-B	12W	AC85-265V	1pc	CREE COB LIFUD DRIVER	WW>80 PW>72	3000K-5000K	630-700Lm	13° / 30°	L=190mm * W=190mm Cut-out=150 * 150mm	2,200.00
BPS-GL-1X20W-B	20W	AC85-265V	1pc		WW>80 PW>72	3000K-5000K	900-1000Lm	13°	L=195mm * W=195mm Cut-out=160 * 160mm	3,600.00
BPS-GL-1X30W-B	30W	AC85-265V	1pc		WW>80 PW>72	3000K-5000K	1350-1500Lm	24°	L=195mm * W=195mm Cut-out=160 * 160mm	3,800.00
BPS-GL-1X40W-B	40W	AC85-265V	1pc		WW>80 PW>72	3000K-5000K	3150-3500Lm	60°	L=195mm * W=195mm Cut-out=160 * 160mm	4,600.00
BPS-GL-2X12W-B	24W	AC85-265V	2pcs	CREE COB LIFUD DRIVER	WW>80 PW>72	3000K-5000K	1260-1400Lm	13° / 30°	L=350mm * W=190mm Cut-out=310 * 150mm	4,200.00
BPS-GL-2X20W-B	40W	AC85-265V	2pcs		WW>80 PW>72	3000K-5000K	1800-2000Lm	13°	L=375mm * W=195mm Cut-out=345 * 160mm	6,800.00
BPS-GL-2X30W-B	60W	AC85-265V	2pcs		WW>80 PW>72	3000K-5000K	2700-3000Lm	24°	L=375mm * W=195mm Cut-out=345 * 160mm	7,000.00
BPS-GL-2X40W-B	80W	AC85-265V	2pcs		WW>80 PW>72	3000K-5000K	6300-7000Lm	60°	L=375mm * W=195mm Cut-out=345 * 160mm	8,600.00
BPS-GL-3X12W-B	36W	AC85-265V	3pcs	CREE COB LIFUD DRIVER	WW>80 PW>72	3000K-5000K	1890-2100Lm	13° / 30°	L=490mm * W=190mm Cut-out=460 * 150mm	6,200.00
BPS-GL-3X20W-B	60W	AC85-265V	3pcs		WW>80 PW>72	3000K-5000K	2700-3000Lm	13°	L=505mm * W=195mm Cut-out=475 * 160mm	10,200.00
BPS-GL-3X30W-B	90W	AC85-265V	3pcs		WW>80 PW>72	3000K-5000K	4050-4500Lm	24°	L=505mm * W=195mm Cut-out=475 * 160mm	10,600.00
BPS-GL-3X40W-B	120W	AC85-265V	3pcs		WW>80 PW>72	3000K-5000K	9450-10500Lm	60°	L=505mm * W=195mm Cut-out=475 * 160mm	13,300.00

Prices are subject to change without prior notice.


PULL-OUT DOWNLIGHT AND FULLY DIRECTIONAL DOWNLIGHT SERIES

BPS-002-2.5F-7W

BPS-002-4F-15W

BPS-002-5F-30W

BPS-002-6F-40W

BKW-DLE05-20W

BKW-DLE05-25W

BKW-DLE05-30W

BKW-DLE06-35W

BKW-DLE06-40W

BKW-DLE06-45W

Model	LED Power	Input Voltage	LED Qty.	LED Chip / Driver	CRI (Ra>)	Color Temperature	Lumen	Beam Angle	Dimension	SRP as of JUNE 2017
BPS-002-2.5F-7W	7W	AC100-240V	1pc	CREE COB LIFUD DRIVER	WW>80 PW>72	2700K-6500K	665-735Lm	24°	D=85 * H=80mm Cut-Out=78mm	1,950.00
BPS-002-4F-15W	15W	AC100-240V	1pc		WW>80 PW>72	2700K-6500K	1425-1575Lm	24°	D=130 * H=115mm Cut-Out=110mm	2,500.00
BPS-002-5F-30W	30W	AC100-240V	1pc		WW>80 PW>72	2700K-6500K	2850-3150Lm	24°/40° 60°	D=165 * H=143mm Cut-Out=155mm	4,300.00
BPS-002-6F-40W	40W	AC100-240V	1pc		WW>80 PW>72	2700K-6500K	3800-4200Lm	24°/40° 60°	D=190 * H=155mm Cut-Out=175mm	5,300.00
BKW-DLE05-20W	20W	AC100-240V	1pc	CITIZEN COB LIFUD DRIVER	WW>83 PW>75	3000K-5000K	2200-2300Lm	25°	D=172 * H=92mm Cut-Out=155mm	4,400.00
BKW-DLE05-25W	25W	AC100-240V	1pc		WW>83 PW>75	3000K-5000K	2750-2875Lm	25°	D=172 * H=92mm Cut-Out=155mm	4,550.00
BKW-DLE05-30W	30W	AC100-240V	1pc		WW>83 PW>75	3000K-5000K	3300-3450Lm	25°	D=172 * H=92mm Cut-Out=155mm	4,650.00
BKW-DLE06-35W	35W	AC100-240V	1pc	CITIZEN COB LIFUD DRIVER	WW>83 PW>75	3000K-5000K	3850-4025Lm	15°/24° 36°/45°	D=190 * H=103mm Cut-Out=175mm	6,550.00
BKW-DLE06-40W	40W	AC100-240V	1pc		WW>83 PW>75	3000K-5000K	4400-4600Lm	15°/24° 36°/45°	D=190 * H=103mm Cut-Out=175mm	7,050.00
BKW-DLE06-45W	45W	AC100-240V	1pc		WW>83 PW>75	3000K-5000K	4950-5175Lm	15°/24° 36°/45°	D=190 * H=103mm Cut-Out=175mm	7,750.00

Prices are subject to change without prior notice.



COB LED DIRECTIONAL OR FIX DOWNLIGHT C3 SERIES



BPS-DL-7W-C3



BPS-DL-12W-C3



BPS-DL-15W-C3



BPS-DL-20W-C3



BPS-DL-30W-C3



BPS-DL-40W-C3



BPS-DL-50W-C3



BPS-DL-60W-C3

Model	LED Power	Input Voltage	LED Qty.	LED Chip / Driver	CRI (Ra>)	Color Temperature	Lumen	Beam Angle	Dimension	SRP as of JUNE 2017
BPS-DL-7W-C3	7W	AC200-240V	1pc	CREE Chip BOKE Driver	WW>82 PW>75	3000K~5000K	700-770Lm	30°	D-95mm - H-59mm Cut-Out - 70mm	1,400.00
BPS-DL-12W-C3	12W	AC200-240V	1pc		WW>82 PW>75	3000K~5000K	1200-1320Lm	24° 35°	D-111mm - H-88mm Cut-Out - 80mm	1,600.00
BPS-DL-15W-C3	15W	AC200-240V	1pc		WW>82 PW>75	3000K~5000K	1500-1650Lm	15°, 24° 38°, 60°	D-118mm - H-103mm Cut-Out - 90mm	2,000.00
BPS-DL-20W-C3	20W	AC200-240V	1pc		WW>82 PW>75	3000K~5000K	2000-2200Lm	15°, 24° 39°, 60°	D-142mm - H-118mm Cut-Out - 110mm	2,500.00
BPS-DL-30W-C3	30W	AC200-240V	1pc		WW>82 PW>75	3000K~5000K	3000-3200Lm	15°, 24° 39°, 60°	D-142mm - H-188mm Cut-Out - 110mm	2,800.00
BPS-DL-40W-C3	40W	AC200-240V	1pc		WW>82 PW>75	3000K~5000K	4000-4400Lm	15°, 24° 39°, 60°	D-180mm - H-128mm Cut-Out - 145mm	4,000.00
BPS-DL-50W-C3	50W	AC200-240V	1pc		WW>82 PW>75	3000K~5000K	5000-5500Lm	15°, 24° 39°, 60°	D-180mm - H-128mm Cut-Out - 158mm	4,800.00
BPS-DL-60W-C3	60W	AC200-240V	1pc		WW>82 PW>75	3000K~5000K	5000-5500Lm	24° 39°, 60°	D-194mm - H-149mm Cut-Out - 158mm	6,000.00

Prices are subject to change without prior notice.



COB LED ROUND AND SQUARE FIX DOWNLIGHT C20 SERIES



BPS-DL-5W-C20-R
BPS-DL-7W-C20-R



BPS-DL-9W-C20-R
BPS-DL-12W-C20-R



BPS-DL-15W-C20-R
BPS-DL-20W-C20-R



BPS-DL-30W-C20-R
BPS-DL-40W-C20-R



BPS-DL-50W-C20-R
BPS-DL-60W-C20-R



BPS-DL-5W-C20-S
BPS-DL-7W-C20-S



BPS-DL-9W-C20-S
BPS-DL-12W-C20-S



BPS-DL-15W-C20-S



BPS-DL-20W-C20-S



BPS-DL-30W-C20-S

Model	LED Power	Input Voltage	LED Qty.	LED Chip / Driver	CRI (Ra>)	Color Temperature	Lumen	Beam Angle	Dimension	SRP as of JUNE 2017
BPS-DL-5W-C20-R	5W	AC100-240V	1pc	ROUND MODEL	WW>82 PW>75	3000K~5000K	500-550Lm	30°	D-95mm - H-63mm Cut-Out - 75mm	1,300.00
BPS-DL-7W-C20-R	7W	AC100-240V	1pc		WW>82 PW>75	3000K~5000K	700-770Lm	30°	D-95mm - H-73mm Cut-Out - 75mm	1,400.00
BPS-DL-9W-C20-R	9W	AC100-240V	1pc		WW>82 PW>75	3000K~5000K	900-990Lm	30°	D-95mm - H-73mm Cut-Out - 75mm	1,500.00
BPS-DL-12W-C20-R	12W	AC100-240V	1pc		WW>82 PW>75	3000K~5000K	1200-1320Lm	24° 40°, 60°	D-115mm - H-83mm Cut-Out - 95mm	1,700.00
BPS-DL-15W-C20-R	15W	AC100-240V	1pc		WW>82 PW>75	3000K~5000K	1500-1650Lm	24° 40°, 60°	D-115mm - H-83mm Cut-Out - 95mm	2,000.00
BPS-DL-20W-C20-R	20W	AC100-240V	1pc		WW>82 PW>75	3000K~5000K	2000-2200Lm	24° 40°, 60°	D-142mm - H-101mm Cut-Out - 125mm	2,500.00
BPS-DL-30W-C20-R	30W	AC100-240V	1pc		WW>82 PW>75	3000K~5000K	3000-3200Lm	24° 40°, 60°	D-160mm - H-133mm Cut-Out - 140mm	3,200.00
BPS-DL-40W-C20-R	40W	AC100-240V	1pc		WW>82 PW>75	3000K~5000K	4000-4400Lm	24° 40°, 60°	D-160mm - H-133mm Cut-Out - 140mm	3,700.00
BPS-DL-50W-C20-R	50W	AC100-240V	1pc		WW>82 PW>75	3000K~5000K	5000-5500Lm	24° 40°, 60°	D-185mm - H-136mm Cut-Out - 160mm	4,700.00
BPS-DL-60W-C20-R	60W	AC100-240V	1pc		WW>82 PW>75	3000K~5000K	6000-6600Lm	24° 40°, 60°	D-230mm - H-140mm Cut-Out - 200mm	5,900.00
BPS-DL-80W-C20-R	80W	AC100-240V	1pc		WW>82 PW>75	3000K~5000K	8000-8800Lm	24° 40°, 60°	D-230mm - H-176mm Cut-Out - 200mm	12,800.00
BPS-DL-5W-C20-S	5W	AC100-240V	1pc	SQUARE MODEL	WW>82 PW>75	2700K~6500K	500-550Lm	12°, 24°	92*92 * H=76mm Cut-Out= 72*72mm	1,500.00
BPS-DL-7W-C20-S	7W	AC100-240V	1pc		WW>82 PW>75	2700K~6500K	700-770Lm	12°, 24°	92*92 * H=76mm Cut-Out= 72*72mm	1,600.00
BPS-DL-9W-C20-S	9W	AC100-240V	1pc		WW>82 PW>75	2700K~6500K	900-990Lm	12°, 24°	92*92 * H=88mm Cut-Out= 72*72mm	1,750.00
BPS-DL-12W-C20-S	12W	AC100-240V	1pc		WW>82 PW>75	2700K~6500K	1200-1320Lm	12°, 24°	92*92 * H=96mm Cut-Out= 72*72mm	2,000.00
BPS-DL-15W-C20-S	15W	AC100-240V	1pc		WW>82 PW>75	2700K~6500K	1500-1650Lm	12°, 24°	112*112 * H=83mm Cut-Out= 95*95mm	2,400.00
BPS-DL-20W-C20-S	20W	AC100-240V	1pc		WW>82 PW>75	2700K~6500K	2000-2200Lm	12°, 24°	112*112 * H=83mm Cut-Out= 95*95mm	3,050.00
BPS-DL-30W-C20-S	30W	AC100-240V	1pc		WW>82 PW>75	2700K~6500K	3000-3200Lm	12°, 24°	142*142 * H=128mm Cut-Out= 125*125mm	4,000.00

Prices are subject to change without prior notice.



BPS-DL-15W-C16-4i



BPS-DL-20W-C16-4i



BPS-DL-20W-C16-6i



BPS-DL-30W-C16-6i



BPS-DL-30W-C16-8i



BPS-DL-40W-C16-8i



BPS-DL-50W-C16-8i



BPS-DL-60W-C16-8i

Model	LED Power	Input Voltage	LED Qty.	LED Chip / Driver	CRI (Ra>)	Color Temperature	Lumen	Beam Angle	Dimension	SRP as of JUNE 2017
BPS-DL-15W-C16-4i	15W	AC85-265V	1pc	CREE COB LIFUD DRIVER	WW>82 PW>75	3000K~5000K	1500-1700Lm	120°	D=110 * H=53mm Cut-Out= 95mm	3,200.00
BPS-DL-20W-C16-4i	20W	AC85-265V	1pc		WW>82 PW>75	3000K~5000K	2000-2200Lm	120°	D=145 * H=69mm Cut-Out= 125mm	3,300.00
BPS-DL-20W-C16-6i	20W	AC85-265V	1pc	CITIZEN COB LIFUD DRIVER	WW>82 PW>75	3000K~5000K	2000-2200Lm	120°	D=190 * H=86mm Cut-Out= 165mm	5,400.00
BPS-DL-30W-C16-6i	30W	AC85-265V	1pc		WW>82 PW>75	3000K~5000K	3000-3300Lm	120°	D=190 * H=86mm Cut-Out= 165mm	5,600.00
BPS-DL-30W-C16-8i	30W	AC85-265V	1pc		WW>82 PW>75	3000K~5000K	3000-3300Lm	120°	D=230 * H=99mm Cut-Out= 200mm	6,800.00
BPS-DL-40W-C16-8i	40W	AC85-265V	1pc		WW>82 PW>75	3000K~5000K	4000-4400Lm	120°	D=230 * H=99mm Cut-Out= 200mm	7,000.00
BPS-DL-50W-C16-8i	50W	AC85-265V	1pc		WW>82 PW>75	3000K~5000K	5000-5500Lm	120°	D=230 * H=99mm Cut-Out= 200mm	7,800.00
BPS-DL-60W-C16-8i	60W	AC85-265V	1pc		WW>82 PW>75	3000K~5000K	6000-6600Lm	120°	D=230 * H=99mm Cut-Out= 200mm	8,000.00

Prices are subject to change without prior notice.


9 & 11-INCHES COB DOWN LIGHT SERIES

BKW-DLC08-22W-B

BKW-DLC08-28W-B

BKW-DLC08-38W-B

BKW-DLC08-50W-B

BKW-DLC08-60W-B

BKW-DLC08-70W-B

BKW-DLC10-22W-B

BKW-DLC10-28W-B

BKW-DLC10-38W-B

BKW-DLC10-50W-B

BKW-DLC10-60W-B

BKW-DLC10-70W-B

Model	LED Power	Input Voltage / Driver	LED Qty.	LED Chip	CRI (Ra>)	Color Temperature	Lumen	Beam Angle	Dimension 9 Inches 11 Inches	SRP as of JUNE 2017
BKW-DLC08-22W-B	22W	AC100-240V LIFUD	1pc	COB CITIZEN	WW>82 PW>75	3000K / 4000K 5000K	2156-2420Lm	25° 45°/ 55°	D=230mm * H=157mm Cut-Out = 215mm	5,300.00
BKW-DLC08-28W-B	28W	AC100-240V LIFUD	1pc	COB CITIZEN	WW>82 PW>75	3000K / 4000K 5000K	2744-3080Lm	25° 45°/ 55°	D=230mm * H=157mm Cut-Out = 215mm	5,600.00
BKW-DLC08-38W-B	38W	AC100-240V LIFUD	1pc	COB CITIZEN	WW>82 PW>75	3000K / 4000K 5000K	3724-4180Lm	25° 45°/ 55°	D=230mm * H=172mm Cut-Out = 215mm	5,850.00
BKW-DLC08-50W-B	50W	AC100-240V LIFUD	1pc	COB CITIZEN	WW>82 PW>75	3000K / 4000K 5000K	4900-5500Lm	25° 45°/ 55°	D=230mm * H=192mm Cut-Out = 215mm	9,900.00
BKW-DLC08-60W-B	60W	AC100-240V LIFUD	1pc	COB CITIZEN	WW>82 PW>75	3000K / 4000K 5000K	5880-6600Lm	36°/ 55°	D=230mm * H=212mm Cut-Out = 215mm	10,300.00
BKW-DLC08-70W-B	70W	AC100-240V MEANWELL	1pc	COB CITIZEN	WW>82 PW>75	3000K / 4000K 5000K	6860-7700Lm	36°/ 55°	D=230mm * H=212mm Cut-Out = 215mm	11,200.00
BKW-DLC10-22W-B	22W	AC100-240V LIFUD	1pc	COB CITIZEN	WW>82 PW>75	3000K / 4000K 5000K	2156-2420Lm	25°/ 40°	D=280mm * H=188mm Cut-Out = 245mm	6,400.00
BKW-DLC10-28W-B	28W	AC100-240V LIFUD	1pc	COB CITIZEN	WW>82 PW>75	3000K / 4000K 5000K	2744-3080Lm	25°/ 40°	D=280mm * H=188mm Cut-Out = 245mm	7,500.00
BKW-DLC10-38W-B	38W	AC100-240V LIFUD	1pc	COB CITIZEN	WW>82 PW>75	3000K / 4000K 5000K	3724-4180Lm	25°/ 40°	D=280mm * H=203mm Cut-Out = 245mm	7,800.00
BKW-DLC10-50W-B	50W	AC100-240V MEANWELL	1pc	COB CITIZEN	WW>82 PW>75	3000K / 4000K 5000K	4900-5500Lm	25°/ 40°	D=280mm * H=223mm Cut-Out = 245mm	10,950.00
BKW-DLC10-60W-B	60W	AC100-240V MEANWELL	1pc	COB CITIZEN	WW>82 PW>75	3000K / 4000K 5000K	5880-6600Lm	25°/ 40°	D=280mm * H=243mm Cut-Out = 245mm	11,600.00
BKW-DLC10-70W-B	70W	AC100-240V MEANWELL	1pc	COB CITIZEN	WW>82 PW>75	3000K / 4000K 5000K	6860-7700Lm	25°/ 40°	D=280mm * H=243mm Cut-Out = 245mm	12,400.00

Prices are subject to change without prior notice.



SURFACE MOUNTED DOWNLIGHT SERIES



BPS-SDL-3-15W



BPS-SDL-4-25W



BPS-SDL-5-35W



BPS-SDL-6-45W



BPS-SDL-3S-20W



BPS-SDL-4S-30W



BPS-SDL-5S-40W

Model	LED Power	Input Voltage	LED Qty.	LED Chip / Driver	CRI (Ra>)	Color Temperature	Lumen	Beam Angle	Dimension	SRP as of JUNE 2017
BPS-SDL-3-15W	15W	AC100-240V	1pc	CITIZEN COB LIFUD DRIVER	WW>80 PW>72	3000K-6000K	1425-1575Lm	60° / 90°	D=110mm H=120mm	1,600.00
BPS-SDL-4-25W	25W	AC100-240V	1pc		WW>80 PW>72	3000K-6000K	2375-2625Lm	60° / 90°	D=130mm H=152mm	1,800.00
BPS-SDL-5-35W	35W	AC100-240V	1pc		WW>80 PW>72	3000K-6000K	3325-3675Lm	60° / 90°	D=170mm H=185mm	2,100.00
BPS-SDL-6-45W	45W	AC100-240V	1pc		WW>80 PW>72	3000K-6000K	4275-4725Lm	60° / 90°	D=193mm H=193mm	2,300.00
BPS-SDL-3S-20W	20W	AC100-240V	1pc		WW>80 PW>72	3000K-6000K	1900-2100Lm	60° / 90°	L=130 x W=130mm H=135mm	2,800.00
BPS-SDL-4S-30W	30W	AC100-240V	1pc		WW>80 PW>72	3000K-6000K	2850-3150Lm	60° / 90°	L=130 x W=130mm H=135mm	3,600.00
BPS-SDL-5S-40W	40W	AC100-240V	1pc		WW>80 PW>72	3000K-6000K	3800-4200Lm	60° / 90°	L=130 x W=130mm H=135mm	4,200.00

Prices are subject to change without prior notice.



COB TRACK LIGHT SERIES



BPS-TL-7W-X1



BPS-TL-10W-X1



BPS-TL-20W-X1



BPS-TL-30W-X1



BPS-TL-20W-X3



BPS-TL-30W-X3



BPS-TL-40W-X3



BPS-TL-50W-X3

Model	LED Power	Input Voltage	LED Qty.	LED Chip / Driver	CRI (Ra>)	Color Temperature	Lumen	Beam Angle	Dimension	SRP as of JUNE 2017
BPS-TL-7W-X1	7W	AC100-240V	1pc	EPISTAR COB BOKE DRIVER	WW>80 PW>72	3000K~5000K	630-770Lm	15° / 24° 36° / 60°	D=63mm H=147mm	1,500.00
BPS-TL-10W-X1	10W	AC100-240V	1pc		WW>80 PW>72	3000K~5000K	950-1050Lm	15° / 24° 36° / 60°	D=63mm H=147mm	1,600.00
BPS-TL-20W-X1	20W	AC100-240V	1pc		WW>80 PW>72	3000K~5000K	1900-2100Lm	15° / 24° 36° / 60°	D=85mm H=165mm	2,050.00
BPS-TL-30W-X1	30W	AC100-240V	1pc		WW>80 PW>72	3000K~5000K	2800-3100Lm	15° / 24° 36° / 60°	D=95mm H=180mm	2,200.00
BPS-TL-20W-X3	20W	AC100-240V	1pc	CITIZEN COB BOKE DRIVER		3000K~6000K	2000-2200Lm	10° / 24° / 38°	90mm 134mm 169mm	4,250.00
BPS-TL-30W-X3	30W	AC100-240V	1pc			3000K~6000K	3000-3300Lm	10° / 24° / 38°	90mm 134mm 169mm	4,400.00
BPS-TL-40W-X3	40W	AC100-240V	1pc			3000K~6000K	4000-4400Lm	10° / 24° / 38°	90mm 134mm 169mm	5,400.00

Prices are subject to change without prior notice.



LED TUBE LIGHT SERIES(UL Listed Also Available)



BWS-T5B-212B-8W



BWS-T5B-213B-14W



BWS-T5B-214B-18W
BWS-T5B-214B-22W



BBD-T8-2FUA-8WB



BBD-T8-4FUA-16WB



BBD-T8-4FUA-18WB



BBD-T8-4FUA-20WB



BBD-T8-4FUA-22WB



T8 Emergency Light

BLD-EMT8-2FT-10W
BLD-EMT8-4FT-18W



T5 Emergency Light

BLD-EMT5-2FT-10W
BLD-EMT5-4FT-18W

Model	LED Power	Input Voltage	LED Qty. LED Type	LED Chip Brand	CRI (Ra)	Color Temperature	Lumen	Size	SRP as of JUNE 2017	
									Non Dimmable	Dimmable
BWS-T5B-212B-8W	8W	AC85-265V	60pcs SMD2835	EPISTAR	WW>85 PW>80	2800K~6500K	850-920Lm	L=600mm D=26mm	930.00	1,100.00
BWS-T5B-213B-14W	14W	AC85-265V	96pcs SMD2835	EPISTAR	WW>85 PW>80	2800K~6500K	1450-1500Lm	L=900mm D=26mm	1,000.00	1,200.00
BWS-T5B-214B-18W	18W	AC85-265V	110pcs SMD2835	EPISTAR	WW>85 PW>80	2800K~6500K	1850-1900Lm	L=1200mm D=26mm	1,200.00	1,400.00
BWS-T5B-214B-22W	22W	AC85-265V	120pcs SMD2835	EPISTAR	WW>85 PW>80	2800K~6500K	2250-2300Lm	L=1200mm D=26mm	1,250.00	1,450.00
BBD-T8-2FUA-8WB	8W	AC85-265V AC100-277V	72pcs SMD2835	EPISTAR	WW>85 PW>80	2800K~6500K	810-900Lm	L=603mm D=26mm	750.00	1,000.00
BBD-T8-4FUA-16WB	16W	AC85-265V AC100-277V	160pcs SMD2835	EPISTAR	WW>85 PW>80	2800K~6500K	1440-1600Lm	L=1198mm D=26mm	1,050.00	1,300.00
BBD-T8-4FUA-18WB	18W	AC85-265V AC100-277V	160pcs SMD2835	EPISTAR	WW>85 PW>80	2800K~6500K	1620-1800Lm	L=1198mm D=26mm	1,100.00	1,350.00
BBD-T8-4FUA-20WB	20W	AC85-265V AC100-277V	200pcs SMD2835	EPISTAR	WW>85 PW>80	2800K~6500K	1980-2200Lm	L=1198mm D=26mm	1,200.00	1,450.00

SRP As of JUNE 2017	4,600.00	6,200.00	4,800.00	6,400.00
Model:	BLD-EMT8-2FT-10W	BLD-EMT8-4FT-18W	BLD-EMT5-2FT-10W	BLD-EMT5-4FT-18W
Input Voltage:	100-277V-AC / 50-60Hz		100-277V-AC / 50-60Hz	
LED Power:	10 Watts	18 Watts	10 Watts	18 Watts
Emergency Power:	8 Watts	15 Watts	8 Watts	15 Watts
Average Working Time:	5 hours	5 hours	5 hours	5 hours
Charging Time:	5-6 hours	5-6 hours	5-6 hours	5-6 hours
LED Quantity / Type:	56pcs SMD2835	110pcs SMD2835	56pcs SMD2835	110pcs SMD2835
LED Brand:	EPISTAR	EPISTAR	EPISTAR	EPISTAR
Lumens:	1080Lm	1900Lm	1080Lm	1900Lm
Color Temperature:	3000K-6500K		3000K-6500K	
Protection Grade:	IP44		IP44	
Dimension:	L=600mm x D=30mm	L=1200mm x D=30mm	L=598mm x D=30mm	L=1198mm x D=30mm
Battery Type:	Slim Type - 18.5V 800mAH Li-Polymer	Slim Type - 30V 800mAH Li-Polymer	Slim Type - 18.5V 800mAH Li-Polymer	Slim Type - 30V 800mAH Li-Polymer
Material:	Aluminum + PC Cover		Aluminum + PC Cover	



ROUND PANEL LIGHT SERIES (SURFACE AND RECESSED MOUNTED)



BJT-PDL-RO-3W



BJT-PDL-RO-6W



BJT-PDL-RO-9W



BJT-PDL-RO-12W



BJT-PDL-RO-15W



BJT-PDL-RO-18W



BJT-PDL-RO-20W




BJT-PDL-RO-24W

Model Recess or Surface	LED Power	Input Voltage	LED Qty.	Light Source	CRI (Ra)	Color Temperature	Lumen	SIZE	SRP as of JUNE 2017
BJT-PDL-RO-3W-R BJT-PDL-RO-3W-S	3W	AC85-265V	15pcs	SMD2835 EPISTAR	WW>80 PW>70	3000K~6000K	270-300Lm	D=90 x 15mm	600.00
BJT-PDL-RO-6W-R BJT-PDL-RO-6W-S	6W	AC85-265V	30pcs	SMD2835 EPISTAR	WW>80 PW>70	3000K~6000K	540-600Lm	D=120 x 15mm	800.00
BJT-PDL-RO-9W-R BJT-PDL-RO-9W-S	9W	AC85-265V	45pcs	SMD2835 EPISTAR	WW>80 PW>70	3000K~6000K	810-900Lm	D=150 x 15mm	1,100.00
BJT-PDL-RO-12W-R BJT-PDL-RO-12W-S	12W	AC85-265V	60pcs	SMD2835 EPISTAR	WW>80 PW>70	3000K~6000K	1080-1200Lm	D=170 x 15mm	1,350.00
BJT-PDL-RO-15W-R BJT-PDL-RO-15W-S	15W	AC85-265V	70pcs	SMD2835 EPISTAR	WW>80 PW>70	3000K~6000K	1350-1500Lm	D=200 x 15mm	1,600.00
BJT-PDL-RO-18W-R BJT-PDL-RO-18W-S	18W	AC85-265V	90pcs	SMD2835 EPISTAR	WW>80 PW>70	3000K~6000K	1620-1800Lm	D=225 x 15mm	1,900.00
BJT-PDL-RO-20W	20W	AC85-265V	100pcs	SMD2835 EPISTAR	WW>80 PW>70	3000K~6000K	1800-2000Lm	D=240 x 15mm	2,300.00
BJT-PDL-RO-24W	24W	AC85-265V	120pcs	SMD2835 EPISTAR	WW>80 PW>70	3000K~6000K	2160-2400Lm	D=300 x 15mm	3,400.00

Prices are subject to change without prior notice.



SQUARE & RECTANGULAR PANEL LIGHT SERIES (SURFACE AND RECESSED MOUNTED)



BJT-PDL-SQ-3W



BJT-PDL-SQ-6W



BJT-PDL-SQ-9W



BJT-PDL-SQ-12W



BJT-PDL-SQ-15W



BJT-PDL-SQ-18W
BJT-PDL-SQ-20W



BJT-PDL-SQ-24W



BLD-PDL-SQ-24W



BBL-PDL-SQ-36W
BBL-PDL-SQ-48W



BBL-PDL-RE-36W

Model Recess or Surface	LED Power	Input Voltage	LED Quantity	Light Source	CRI (Ra)	Color Temperature	Lumen	Size	SRP as of JUNE 2017
BJT-PDL-SQ-3W-R BJT-PDL-SQ-3W-S	3W	AC85-265V	15pcs	SMD2835 EPISTAR	WW>80 PW>70	2700K~6500K	270-300Lm	90 x 90 x 15mm	600.00
BJT-PDL-SQ-6W-R BJT-PDL-SQ-6W-S	6W	AC85-265V	30pcs	SMD2835 EPISTAR	WW>80 PW>70	2700K~6500K	540-600Lm	120 x 120 x 15mm	800.00
BJT-PDL-SQ-9W-R BJT-PDL-SQ-9W-S	9W	AC85-265V	45pcs	SMD2835 EPISTAR	WW>80 PW>70	2700K~6500K	810-900Lm	150 x 150 x 15mm	1,100.00
BJT-PDL-SQ-12W-R BJT-PDL-SQ-12W-S	12W	AC85-265V	60pcs	SMD2835 EPISTAR	WW>80 PW>70	2700K~6500K	1080-1200Lm	170 x 170 x 15mm	1,350.00
BJT-PDL-SQ-15W-R BJT-PDL-SQ-15W-S	15W	AC85-265V	70pcs	SMD2835 EPISTAR	WW>80 PW>70	2700K~6500K	1350-1500Lm	200 x 200 x 15mm	1,600.00
BJT-PDL-SQ-18W-R BJT-PDL-SQ-18W-S	18W	AC85-265V	90pcs	SMD2835 EPISTAR	WW>80 PW>70	2700K~6500K	1620-1800Lm	220 x 220 x 15mm	1,900.00
BJT-PDL-SQ-20W-R BJT-PDL-SQ-20W-S	20W	AC85-265V	102pcs	SMD2835 EPISTAR	WW>80 PW>70	2700K~6500K	1800-2000Lm	240 x 240 x 15mm	2,300.00
BJT-PDL-SQ-24W	24W	AC85-265V	120pcs	SMD2835 EPISTAR	WW>80 PW>70	2700K~6500K	2160-2400Lm	300 x 300 x 15mm	3,400.00
BLD-PDL-SQ-24W	24W	AC85-265V	120pcs	SMD2835 EPISTAR	WW>80 PW>70	2700K~6500K	1800-2100Lm	600 x 600 x 15mm	5,300.00
BBL-PDL-SQ-36W	36W	AC85-265V	160pcs	SMD2835 EPISTAR	WW>80 PW>70	2700K~6500K	3240-3600Lm	600 x 600 x 15mm	5,600.00
BBL-PDL-SQ-48W	48W	AC85-265V	180pcs	SMD2835 EPISTAR	WW>80 PW>70	2700K~6500K	3600-4000Lm	600 x 600 x 15mm	6,500.00
BBL-PDL-RE-36W	36W	AC85-265V	160pcs	SMD2835 EPISTAR	WW>80 PW>70	2700K~6500K	3240-3600Lm	300 x 1200 x 15mm	6,000.00

Prices are subject to change without prior notice.